

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented)                      A method, comprising:

interfacing an identity oriented context application that represents a context of an identity based on an availability of the identity with a device oriented context application that provides an availability of a device associated with the identity, where the identity is a person or a group of persons;

detecting a new device oriented context provided by said device oriented context application for a specific device associated with an identity, wherein said new device oriented context provides an availability status of the specific device and the identity oriented context application and the device oriented context application are separate and distinct from each other;

mapping said new device oriented context provided by said device oriented context application to an identity oriented context for said identity by said identity oriented context application by associating the new device oriented context with said identity oriented context, wherein said identity oriented context provides an availability status of said identity; and

providing data indicative of said mapped identity oriented context to said identity context oriented application.

2. (Previously Presented)                      The method of claim 1, wherein said detecting said new device oriented context for said device includes detecting said new device oriented context in a presence and availability service.

3. (Previously Presented)                      The method of claim 1, wherein said detecting said new device oriented context for said device includes receiving a request to change

said device's device context.

4. (Previously Presented) The method of claim 1, wherein said mapping said new device oriented context to said identity oriented context for said identity includes determining said identity.

5. (Previously Presented) The method of claim 1, wherein said mapping said new device oriented context to said identity oriented context for said identity includes determining said identity context.

6. (Previously Presented) The method of claim 1, further comprising determining said identity.

7. (Previously Presented) The method of claim 1, further comprising determining said identity context.

8. (Canceled)

9. (Canceled)

10. (Previously Presented) The method of claim 1, further comprising:  
  
receiving a request to make a change to a new identity oriented context for an identity; and

mapping said new identity oriented context to a device context for a device associated with said identity.

11. (Previously Presented) The method of claim 1, further comprising:  
  
receiving a request to make a change to a new identity oriented context for a second identity; and

mapping said new identity oriented context to a device oriented context for a device associated with said second identity.

12. (Previously Presented)            The method of claim 11, wherein said receiving said request to make said change to a new identity oriented context for said second identity includes receiving said request from an identity context oriented application.

13. (Previously Presented)            The method of claim 11, wherein said mapping said new identity oriented context to said device context for said device associated with said second identity includes determining said device associated with said second identity.

14. (Previously Presented)            The method of claim 13, wherein said mapping said new identity oriented context to said device context for said device associated with said second identity includes determining said device oriented context associated with said device associated with said second identity.

15. (Previously Presented)            The method of claim 11, wherein said mapping said new identity oriented context to said device context for said device associated with said second identity includes accessing a mapping table.

16. (Previously Presented)            The method of claim 1, further comprising:  
  
providing data indicative of said device oriented context to a presence and availability service.

17. (Previously Presented)            The method of claim 11, further comprising:  
  
changing an identity oriented context for said second identity from a first identity oriented context to a said new identity oriented context in response to said request.

18. (Previously Presented)            A method, comprising:  
  
interfacing an identity oriented context application that represents a context of an identity based on an availability of the identity with a device oriented context application

that provides an availability of a device associated with the identity, where the identity is a person or a group of persons;

detecting a new device oriented context provided by said device oriented context application for a specific device in a presence and availability service, wherein said new device oriented context is associated with an identity and provides an availability status of the specific device and the identity oriented context application and the device oriented context application are separate and distinct from each other;

mapping said new device oriented context provided by said device oriented context application to an identity oriented context for said identity by said identity oriented context application by associating the new device oriented context with said identity oriented context, wherein said identity oriented context provides an availability status of said identity;

providing data indicative of said mapped identity oriented context to a said identity context oriented application.

19. (Previously Presented) An article of manufacture comprising:

a computer readable medium having stored thereon instructions which, when executed by a processor, cause said processor to:

interface an identity oriented context application that provides an availability of the identity with a device oriented context application that represents the context of identity based on an availability of a device associated with the identity, where the identity is a person or a group of persons;

detect a new device oriented context for a specific device associated with an identity, wherein said new device oriented context provides an availability status of the specific device and the identity oriented context application and the device oriented context application are separate and distinct from each other;

map said new device oriented context provided by said device oriented

context application to an identity oriented context for said identity by said identity oriented context application by associating the new device oriented context with said identity oriented context, wherein said identity oriented context provides an availability status of said identity; and

provide data indicative of said mapped identity oriented context to an said identity context oriented application.

20. (Previously Presented) An apparatus, including:

a processor;

a communication port coupled to said processor and adapted to communicate with at least one device; and

a storage device coupled to said processor and storing instructions adapted to be executed by said processor to:

interface an identity oriented context application that represents a context of an identity based on an availability of the identity with a device oriented context application that provides an availability of a device associated with the identity, where the identity is a person or a group of persons;

detect a new device oriented context provided by said device oriented context application for a specific device associated with an identity, wherein said new device oriented context provides an availability status of the specific device and the identity oriented context application and the device oriented context application are separate and distinct from each other;

map said new device oriented context provided by said device oriented context application to an identity oriented context for said identity by said identity oriented context application by associating the new device oriented context with said identity oriented context for said identity, wherein said identity oriented context provides an availability status of said identity; and

provide data indicative of said mapped identity oriented context to said identity oriented context application.